



CXP-19S-CIIR

Features

- 19" Intel Core i7/i5/i3 Fanless Stainless Panel PC
- IP66 full sealed with Anti-corrosion enclosure
- 19" LCD with full flat Resistive touch
- i-Cooling thermal control system
- Special thermal design with anti-condensation
- IP67 M12 metal connectors
- IP67 power adapter and IP67 external I/O cables
- CE, FCC, VCCI Class B passed
- Optional Mini-PCle WLAN with external antenna
- Optional Sunlight readable with optical bonding



Technical Specifications

LCD

19" LED 1280x 1024

Brightness (cd/m2)

350

Contrast Ratio

1000:1

CPU

Intel Core i7/i5/i3 processor

Memory

Two 204-pin 1333/1600 MHz dual-channel DDR3
SO-DIMM supports up to 16GB

OS Support

Windows

Touch Panel

5 wire Full Flat Resistive Touch

I/O

2 x USB M12 , 2 x COM M12 (RS232)
1 x LAN M12

Dimension (WxHxD)(mm)

458 x 386 x 64

Power

DC 12V

Operating Temperature

0°~40°C

Storage Temperature

-20°~60°C


COMX

17F-10 NO. 79, SEC 1 XINTAI 5th RD.,
XIZHI DIST, 221, NEW TAIPEI CITY
22101 TAIWAN

Tel: +886 2 8698 3608
Fax: +886 2 8698 3606



Technical Drawing



Packing & Options

Packaging

System, power adaptor, AC power cord,
DVD (drivers & manual)


Options

- Wireless or Wireless + BT kit (2 ant)
- M12 to 1x COM cable
- M12 to 1x USB cable (1 USB Port)
- M12 to 2x USB cable (2 USB Ports)
- M12 to 1x LAN cable
- M12 to 1x LAN cable (cable length is 2 meters, Waterproof)
- SSD
- Wall mount / table mount bracket
- 2 EXTERNAL I/O (USB x2, LAN x2, COM x1)

Customization

- 1000 nits high brightness LCD
- Sunlight readable optical bonding
- Anti UV and 7H coating
- Full flat PCT touch screen IP69K
- LCD Auto dimming
- LCD Super dimming (Low brightness)

I/O & Control keys



- 1 Giga Lan
- 2 USB (1/2)
- 3 USB (3/4)
- 4 COM x 2
- 5 DC-in
- 6 Power on/off



Table Mount



Wall Mount