



# CXM-26M

## Features

- 26" Medical display
- Support Multi Display Mode: PIP/PAP
- AR protective filter
- Various video input: D-Sub,VGA, DP, HDMI, SDI Composite (PAL,NTSC), Component (RGBs/YPbPr) and S-Video (PAL/NTSC).
- cTUVus (ANSI/AAMI ES 60601-1, CAN/CSA C22.2 No.606011) CB (60950/60601, CE, FCC Class B part 15 CCC, VCCI, BSMI)



## Technical Specifications

### LCD

26" IPS with LED

### Brightness (cd/m2)

450

### Contrast Ratio

1400:1

### Resolution

1920 x 1200

### Active Screen Area

573 x 324

### Viewing Angle

178°(H) x 178°(V)

### Touch Panel

N/A

### I/O

1 x DVI, 1 x VGA, 1 x HDMI, 1 x DP, 1 x RS232

### Front Frame

Metal

### Dimension (WxHxD)(mm)

651 x 402 x 98.2

### Power

DC 24V

### Operating Temperature

10°~40°C

COMX

17F-10 NO. 79, SEC 1 XINTAI 5th RD.,  
XIZHI DIST, 221, NEW TAIPEI CITY  
22101 TAIWAN

Tel: +886 2 8698 3608  
Fax: +886 2 8698 3606

<http://www.comxpc.com>