



CXI-2UM2

Features

- 19" Rackmount Standard
- Heavy-duty Steel with Ni plating
- Supports ATX Motherboard
- Locable Front Door for Maximum Access Security and Replaceable Air Filter
- (1) PS/2 connector on front panel
- (2) USB ports on front panel
- (2) 8cm Ball-bearing Fans
- Up to 2U 400W Single or 2U 380W Redundant Power supply

Technical Specifications

Optional 18-inch Slide rail

PCIe and PCI slots Riser card

(1) 5.25" and (1) 3.5" Drive bays

(2) 3.5" Drive bays

With replaceable Air Filter

2U Single or Redundant Power supply

Construction

Heavy-duty steel with Ni plating

Color

Black

Board support

ATX motherboard

Drive bays

1 x 5.25" & 1 x 3.5" ext. Drive bays, 2 x 3.5" internal Drive bays

Expansion

Option 1: (3) 32-bit PCI slots, Option 2: (1) 32-bit PCI, (1) PCIe x 16, (1) PCIe x 1 slots Option 2: (2) 32-bit PCI and (1) PCIe x 16 slots

Power supply

Up to 500W 2U single or up to 380W 2U redundant PSU

COMX

17F-10 N0. 79, SEC 1 XINTAI 5th RD., XIZHI DIST, 221, NEW TAIPEI CITY 22101 TAIWAN

Tel: +886 2 8698 3608 Fax: +886 2 8698 3606

Cooling system

Front Door Latch

2 x 80mm ball-bearing fans with replaceable air filter

I/O port

1 x PS/2 connector, 2 x USB 2.0, Power on/off and reset switch

Indicator

Power on/off and HDD activity LEDs

Operating Temperature

0°~50°C

Gross weight

9.4kg

Dimension (mm)

434 x 450 x 88

http://www.comxpc.com